

TAIL CUTTING SYSTEMS

TAIL CUTTER CONTROL

- ✓ Turn key unit.
- ✓ Pre-tested system.
- ✓ Just connect unit power and start-up.
- ✓ Tail cutter can be operated with an external signal (sheet break photocell or alarm buttons).
- Panel interface and motor control center.
 - Stroke limit setting (Encoder version).
 - Display of actual cutting unit position.
 - Alarm display and diagnostic.
 - Dedicated PLC (SIEMENS or ALLEN-BRADLEY).
- Operation and maintenance dedicated code.
- Electric motor control center.
- Push button box located close to the machine
 - Push button "Back Side", "Front Side", "Tail".
 - Push button "Widen", "Narrow" at low speed.
 - Emergency push button "Stop".

TAIL CUTTER CONTROL



WET END TRIM SQUIRTS W-TB

WET END TRIM SQUIRTS W-TB 1



- ✓ Web cut with water jet.
- ✓ Web cutting on Wire.
- ✓ Nozzle check and exchange during production.
- ✓ High operating performance.
- ✓ High reliability and safe operation.
- ✓ Easy installation and reduced maintenance.
- Air shielded nozzle (no formation of moisture deposits).
- Settings
 - Jet impinging angle.
 - Nozzle distance from paper.
 - Nozzle replacement during productions.

WET END TRIM SQUIRTS W-TB 2



- Manual version
 - Position control with manual knob.
 - Position indication with scale and pointer.
- Motorized version
 - Position control with motor and remote control.
 - Digital display of the position.
- Option
 - Single or double nozzle.

WET END TRIM SQUIRTS W-TB 2

