

GUIDING SYSTEMS

VERTICAL GUIDE W-GV

- ✓ Compact and reliable assembly.
- ✓ Low and simple maintenance.
- ✓ Suitable for humid and dry environments.

- Press felt application.
- Roll support linear displacement.
- Execution in stainless steel or painted mild steel.
- Two sizes for different applications.
- Vertical or inclined mounting design.
- Options:
 - execution for high temperature applications.
- Accessories:
 - system for manual positioning;
 - roll support bearing housings;
 - pressure balance palm valve;
 - proportional bleed palm valve;
 - alarm palm.
- For inclined mounting contact Weingrill.

VERTICAL GUIDE W-GV



SIZE	F1 (daN)	STROKE	ØD max (mm)
W-GV8	400	± 35 mm	160
W-GV26	1000	± 35 mm	220
W-GV20	1900	± 35 mm	280



BEARING SEATS W-S

- ✓ Easy roll removal.
- ✓ Suitable for humid and dry environments.

- Stainless steel or painted cast iron execution.
- Model W - S -110
 - Cylindrical seat: diameters from 80 to 110 mm.
 - Spherical seat: diameters from 90 to 110 mm.
- Model W-S-160
 - Cylindrical seat: diameters from 110 to 160 mm.
 - Spherical seat: diameters from 120 to 160 mm.
- Model W-S-200
 - Cylindrical seat: diameters from 170 to 200 mm.
 - Spherical seat: diameters from 180 to 200 mm.
- Other sizes available upon request.

SEAT W-S

